Poly Edge E350 IP Phone and PoE-enabled





*Product image may differ from actual product

A phone with high standards

Easy to use and packed with features, the Poly Edge E300 Series pairs Poly noise reduction technology with cuttingedge design. Whether you're hot-desking at work or calling from your home office, these phones bring style to any desktop.

The new office standard

This phone is outfitted with a bright 3.5-inch color IPS LCD display and shows your lines, features, contacts, speed dials and more.

Integrated protection

Rest assured that your devices stay cleaner for longer with integrated Microban[®] antimicrobial product protection ¹.

Enterprise-quality sound

Enjoy quality audio with the Poly Edge E300 Series plus reduce distractions with Poly NoiseBlockAl and Acoustic Fence technologies.

Featuring

All the features you could ask for

Get fast access features via the main 3.5" color display with a surround light status indicator. 8-line keys support up to 32 lines and contacts.

Versatile connectivity

Two high-speed GigE PoE Ethernet ports for the LAN connection to your IP phone. And a Poly headset: Bluetooth®, USB, RJ9, or Electronic Hook Switch.

Perfectly paired

Move around the office with ease with your Poly Bluetooth[®] headset² and answer your mobile phone calls from your desk phone².

Works wherever you do

Work anywhere with 802.11AC Wi-Fi included. Simple out-ofthe-box configuration gives you peak performance anywhere you've got a signal.

Accessibility is key

Improved accessibility with text-to-speech feature, screen color adjustments for color blindness and bigger font settings.

Noise blocking technology

Poly NoiseBlockAl and Poly Acoustic Fence technologies.

Poly Edge E350 IP Phone and PoE-enabled



Specifications

Display

Aspect ratio: 4:3 Native resolution: 320 x 240 Panel technology: Color IPS LCD Display size (diagonal): 3.5"

Connectivity and communications

External I/O ports: 1 USB 2.0 Type-C* (for media and storage applications) 2 RJ-45 (10/100/1000BASE-TX Mbps) Wireless Technology: Bluetooth* 5.0; Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20); 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40); NFC³

User interface features

Languages: Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

Audio features:

Poly HD Voice

Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression

Poly Acoustic Fence technology eliminates background noise when using a handset or wired headset

Poly NoiseBlockAl technology removes most background noise when using the speakerphone

Poly Computer Audio Connector app installed on your PC (Windows only) enables selecting your phone for PC audio in/out to use the phones handset, optional headset and handsfree speakerphone with PC applications

TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)

Individual volume settings with visual feedback for each audio path

Voice activity detection

Comfort noise generation

DTMF tone generation (RFC 2833 and in-band) Low delay audio packet transmission Adaptive jitter buffers

Frequency response (microphone): 150 Hz to 14 kHz **Audio codecs:** G.711 (A-law and μ-law); G.722; G.729AB; iLBC; OPUS; G.722.1



*Product image may differ from actual product

Other features

Special features: Unicode UTF-8 character support; Adjustable desk stand (2 positions); Wall mountable⁵

Power supply

Power features:13 W (maximum) Built-in auto-sensing IEEE 802.3af Power over Ethernet (Class 3)^{2, 4}

Environmental

Certifications and compliances: AS/NZS 60950.1; AS/NZS 62368.1; Australia RCM; Brazil ANATEL; CAN/CSA C22.2 No. 62368-1-14; CE Mark; CISPR22 Class B; EEA; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN55024; EN55032 Class B; EN 60950-1 & EN 62368-1: FCC Part 15 (CFR 47) Class B: FCC Part 15.247; FCC Part 15.407; IEC 60950-1 & IEC 62368-1; ICES-003 Class B; Israel MOC; Japan MIC/VCCI; Japan Item (19)-3-2; Malaysia SIRIM; NZ Telepermit, R-NZ; ROHS compliant; Saudi Arabia CITC; Singapore IMDA; So. Africa ICASA; So. Korea KC; Taiwan NCC/BSMI; UAE TRA; UL 62368-1; VCCI Class B; Argentina ENACOM; Canada ICES; Canada-RSS 247 Issue2; China SRRC; China RoHS 2.0;India WPC; EU-ETSI EN 300 328 & ETSI EN 301 893; Indonesia SDPPI; Mexico IFETEL and NYCE; UK - UKCA; USA FCC Operating humidity range: 5 to 95% Operating temperature range: 32 to 104°F Storage temperature range: -40 to 160°F Energy star certified: ENERGY STAR® certified



Poly Edge E350 IP Phone and PoE-enabled

Specifications

Management

Management software: Poly Zero Touch Provisioning Poly Lens Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management SDP

Display features

Lightbar status indicator (RGB with color mixing)

Security

Security management: 802.1X Authentication and EAPOL Media encryption via SRTP Digest authentication Encrypted configuration files HTTPS secure provisioning Password login Support for signed software executables Support for URL syntax with password Transport Layer Security (TLS) Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2) SRTP media encryption using AES 256 bits

Headset and handset compatibility

Headset ports: 1RJ-9

1 Electronic Hook Switch (EHS) port for optional APP-51 adapter Headset and handset compatibility: Bluetooth* headset compatibility Compatible with commercially available TTY adapter equipment Compliant with ADA Section 508 Subpart B 1194.23 (all) Hearing aid compatibility to ITU-TP.370 and TIA 504A standards Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids USB Type-C* headset support

Telephony and call handling features

Telephony and call handling features: 4 context-sensitive soft keys 4 way navigation key cluster with center Select key Bundled with Polycom UC Software: Corporate Directory Access using LDAP Busy Lamp Field (BLF) Call timer and call waiting Call transfer, hold, divert (forward), park, pickup Called, calling, connected party information Calling Party Identification (RFC8225 classifications - Trusted, Unknown, SPAM) Distinctive incoming call treatment/call waiting Do not disturb function Electronic hook switch capable Enhanced Feature Keys make powerful feature shortcuts online key appearances or soft keys Headset select key (illuminated when selected) Hold and transfer keys Home and back feature keys Local three-way audio conferencing Local configurable digit map/dial plan Mute key (illuminated when muted) One-touch speed dial, redial Pagination key for additional lines/contacts Remote missed call notification Reverse number lookup via LDAP Shared call/bridged line appearance Speakerphone select key (illuminated when selected) Supports Polycom Apps SDK and API for third- party business and personal application Visual Conference Management Voicemail key Volume +/- control keys Flexible line appearance (one or more line keys can be assigned for each line extension)

8 programmable line keys supporting up to 32 line key assignments for lines, contacts, and features with pagination¹

Network

Supported network protocols: DHCP VLAN discovery LLDP-MED for VLAN discovery FTP/TFTP/HTTP/HTTPS server-based central provisioning Hardware diagnostics Manual or dynamic host configuration protocol (DHCP) network setup Network address translation support for static configuration and Keep-Alive QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP Status and statistics reporting Syslog Event Logging Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation Time and date synchronization using SNTP RTCP and RTP support IPv4 IPv6 Provisioning and call server redundancy support DNS-SRV UDP SIP protocol support IETF SIP (RFC 3261 and companion RFCs) VoIP features: 8 line keys supporting up to 32 SIP lines with pagination

Weight and dimensions

Product Primary Color: White; Midnight blue Package weight: 0.66 lb Package dimensions: 7.48 x 8.26 x 2.16 in Master carton quantity: 5 Master carton dimension: 9.64 x 17.32 x 11.61 in Master carton weight: 11.02 lb Cartons per layer: 10 Pallet (layers): 6 Cartons per pallet: 60 Products per pallet: 60 Products per pallet: 300 Pallet weight: 787.05 lb Pallet dimensions: 40 x 48 x 58.66 in Product number: 82M89AA Product name: Poly Edge E350 IP Phone and PoE-enabled

Warranty

Poly standard one-year limited warranty

Country of origin

Country of origin: Made in China

What is in the box

Setup sheet Network (LAN) cable-CAT-5E Desk stand Console with Microban® Antimicrobial protection Handset with Microban® Antimicrobial protection Handset cord



Poly Edge E350 IP Phone and PoE-enabled

Footnotes

Messaging Footnotes

¹ Microban antimicrobial product protection available for the Poly Edge E Series phones protects the entire phone except for the handset cord. Microban antimicrobial product protection is a built-in active ingredient that enables products to resist the growth of microbes such as bacteria, mold, and mildew. Microban protection helps products stay cleaner, fresher, and last longer than products with untreated surfaces. ² Poly headsets sold separately. Poly Electronic Hook Switch (EHS) sold separately. ³ Poly Edge E Series phones connecting via Wi-Fi must be powered by an optional power supply unit when not powered via PoE.

Technical Specifications Footnotes

¹ Most software-enabled features must be supported by the service provider platform. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features. ² External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately). Power supply unit (PSU) sold separately. ³ NFC-enabled Edge E series phones allow third-party applications to read serial number and other device information that can be useful in application development such as guest login for phone hoteling. ⁴ Ordering an optional power supply unit will be necessary if not powered over ethernet with PoE (i.e. using Wi-Fi for network). ⁵ Optional wall mount kit can be ordered separately.

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

March 2025 us-en

